

ARAVIS-120

FR-LINING

50% META-ARAMID / 50% FR VISCOSE, 120 GSM, PLAIN 1/1
FLAME RETARDANT



CERTIFICATION:

EN 469



PENDING

Aravis FR-liner is designed for fire fighter turnout gear with a new level of moisture management properties. It is light, thin and inherently flame resistant.

SPECIFICATION:

ARTICLE	COMPOSITION	WEIGHT	WEAVE	FULL WIDTH	FINISHES
ARAVIS-120	50% M-ARAMID 50% FR VISCOSE	120 GSM / 3,5 OZ	PLAIN 1/1	151 CM (±1 CM) / 60"	INHERENT FR

PHYSICAL PARAMETERS:

	YARN TYPE	TEARING STRENGTH (ISO 13937-2)	TENSILE STRENGTH (ISO 13934-1)	SHRINKAGE (ISO 6530-2000)
WARP	RING SPUN	10 N	> ? N	≤ - 2%
WEFT	RING SPUN	10 N	> ? N	≤ - 2%

COLOUR FASTNESS TO:

WASHING 60°C (ISO 105 C06)		RUBBING (ISO 105 X12)		DRY CLEANING (ISO 105 D01)	PERSPIRATION (ISO 105 E04)	LIGHT (ISO 105 B02)
COLOUR CHANGE	COLOUR STAINING	DRY	WET	-	-	-
4-5	4-5	4	4-5	4-5	4-5	4

CARE INSTRUCTIONS:



KEEP IN COOL DRY PLACE, WITH NO DIRECT SUNLIGHT

STANDARD COLOURS:



BLACK #X601



ROYAL BLUE #X604




DARK NAVY #X602




GREEN #X609



RED #X603



ORANGE #X606



NAVY #X628